

Problem A. Puzzle: X-Sums Sudoku

Input file: *standard input*
Output file: *standard output*
Time limit: 4 seconds
Memory limit: 256 mebibytes

An $n \times m$ sudoku puzzle is a grid consisting of $m \times n$ regions, and each region contains $n \times m$ cells. Hence an $n \times m$ sudoku puzzle contains $nm \times nm$ cells. Every integer from 1 to nm occurs exactly once in each row, each column, and each region of an $n \times m$ sudoku puzzle.

Listing the integers in a row or a column starting from some direction as a sequence of length nm , X is the first integer of the sequence, and X-sum is the sum of the first X integers of the sequence.

	1	6	11	20	22	32	34	36	
1	1	2	3	4	5	6	7	8	36
8	3	4	1	2	7	8	5	6	29
27	5	6	7	8	1	2	3	4	10
34	7	8	5	6	3	4	1	2	3
3	2	1	4	3	6	5	8	7	34
10	4	3	2	1	8	7	6	5	27
29	6	5	8	7	2	1	4	3	8
36	8	7	6	5	4	3	2	1	1
	36	34	32	22	20	11	6	1	

The above figure is a 4×2 sudoku puzzle with X-sums. The 7-th row listed from right to left is $[3, 4, 1, 2, 7, 8, 5, 6]$ and the first integer X is 3, so the X-sum of the 7-th row from the direction right is $8 = 3 + 4 + 1$.

Given two positive integers n and m , a direction d , and an index x , you need to find the X-sum of the x -th row or x -th column from the direction d in **the lexicographically smallest** $2^n \times 2^m$ sudoku.

Denoting $a_{i,j}$ as the i -th row and the j -th column of a sudoku puzzle a , a sudoku puzzle a is lexicographically smaller than a sudoku puzzle b of the same size if there exists i and j satisfying that $a_{i,j} < b_{i,j}$, that $a_{x,y} = b_{x,y}$ for all $x < i$, and that $a_{x,y} = b_{x,y}$ for all $x = i$ and $y < j$. You can find that the above is the lexicographically smallest 4×2 sudoku puzzle.

Input

There are multiple test cases. The first line of input contains an integer T ($1 \leq T \leq 10^5$), the number of test cases.

For each test case:

The only line contains two integers n and m ($1 \leq n, m \leq 30$), a string d , and an integer x ($1 \leq x \leq 2^{n+m}$). Here, $2^n \times 2^m$ is the size of the sudoku puzzle; d is the direction of X-sum, and it is one of “left”, “right”, “top”, and “bottom”; x is the index of a row or a column.

Output

For each test case:

Output an integer: the X-sum of the x -th row or x -th column from the direction d in **the lexicographically smallest** $2^n \times 2^m$ sudoku.

Note that the answer may exceed $2^{64} - 1$. Consider using `__int128_t` in C++, `BigInteger` in Java or `Kotlin`, or `int` in Python.



Examples

<i>standard input</i>	<i>standard output</i>
4 2 1 top 1 2 1 bottom 2 2 1 left 3 2 1 right 4	1 34 27 3
4 11 19 top 1053766555 12 26 top 230781535210 14 10 right 8344647 7 30 right 70120568170	565741033271081135 31719572400444316026492 112693473538824 477453505821905419941

Problem B. Puzzle: Patrick's Parabox

Input file: *standard input*
Output file: *standard output*
Time limit: 4 seconds
Memory limit: 512 mebibytes

Patrick's Parabox is a *Sokoban*-like game. A Sokoban puzzle is a grid, and each cell is a wall or a floor. There are several boxes and a player in some distinct floor cells, and they can not move to the wall cells or coincide. You can control the player to move in one of four directions, left, right, up, and down. When the player touches a box, it can push the box. The target is to move all boxes to some target cells.

Please read the following rules carefully. They may be different from the usual rules.

In this problem, there is **only one** box, and the box is the grid itself. That means if the player moves out of the grid, they may be “teleported” to a cell adjacent to the box; if the player moves to the box, they may be “teleported” to a cell on the boundary of the grid. Besides, there is also a target cell for the player. The player needs to move to the target cell at the end too.

Given a puzzle, you need to find the **minimum number of times to push** the box, such that the box and the player can arrive to their respective target cells.

The following are the detailed and formal rules.

Consider an $n \times m$ grid. Denote (i, j) as the cell in i -th row and j -th column. The rows are numbered $1, 2, \dots, n$ from top to bottom, and the columns are numbered $1, 2, \dots, m$ from left to right.

Denote W, S, A, and D as the control commands, which mean to move up, down, left, and right respectively.

Define that $v_W = (-1, 0)$, $v_S = (1, 0)$, $v_A = (0, -1)$, $v_D = (0, 1)$.

Define that $w_W = (n, \lceil \frac{m}{2} \rceil)$, $w_S = (1, \lceil \frac{m}{2} \rceil)$, $w_A = (\lceil \frac{n}{2} \rceil, m)$, $w_D = (\lceil \frac{n}{2} \rceil, 1)$.

In each operation, you can choose one of the control commands c , one of W, S, A, and D. Denote p as the cell which contains the player and b as the cell which contains the box before the operation:

- If $p + v_c = b$ and $b + v_c$ is a floor cell, the player moves to $p + v_c$ and the box moves to $b + v_c$. **Only this case** counts towards the answer, and so has to happen the minimum possible number of times.
- If $p + v_c$ is a wall cell, nothing happens.
- If $p + v_c$ is a floor cell and $p + v_c \neq b$, the player moves to $p + v_c$.
- If $p + v_c = b$ and $b + v_c$ is outside the grid, nothing happens.
- If $p + v_c = b$, $b + v_c$ is a wall cell and w_c is a wall cell, nothing happens.
- If $p + v_c = b$, $b + v_c$ is a wall cell and w_c is a floor cell, the player moves to w_c .
- if $p + v_c$ is outside the grid and $b + v_c$ is a wall cell, nothing happens.
- if $p + v_c$ is outside the grid and $b + v_c$ is outside the grid, nothing happens.
- if $p + v_c$ is outside the grid and $b + v_c$ is a floor cell, the player moves to $b + v_c$.

Note that the above are listed for covering all possibilities, but the operations are valid in only four of them (in other cases, nothing happens).

Input

There are multiple test cases. The first line of input contains an integer T ($1 \leq T \leq 10^5$), the number of test cases.

For each test case:

The first line contains two integers n and m ($2 \leq n, m \leq 10^5$), the size of the parabox.

Each of the following n lines contains a string of length m . Each character is one of “#”, “.”, “p”, “b”, “=” and “-”. Here, “#” denotes a wall cell, “p” denotes the floor cell which contains the player, “b” denotes the

floor cell which contains the box, “=” denotes the target floor cell of the player, “-” denotes the target floor cell of the box, and “.” denotes other floor cells.

It is guaranteed that each of “p”, “b”, “=”, “-” occurs exactly once.

It is guaranteed that the sum of $n \cdot m$ over all test cases does not exceed $4 \cdot 10^5$.

Output

For each test case:

If it is impossible to move the box and the player to their respective target cells, output -1. Otherwise, output an integer: the **minimum number of times to push** the box.

Examples

<i>standard input</i>	<i>standard output</i>
<pre> 3 9 9 ##### #####..-# #..=##.## #.p.##.####.## #...b..## #...##.## #...#### ####.#### 9 9 ##### #.....# #.#####.# #.#=....# ..#....-# ###.p.#.# #....#b# #....#.# ####.#### 9 9 ####.#### #...#### #.#####.## #.....# #.....# ###.##### #=.b#..## #-..p..## ##### </pre>	<pre> 7 4 19 </pre>
<pre> 1 2 2 pb -= </pre>	<pre> -1 </pre>

Note

The three puzzles in the first example are real levels in the game.

Problem C. Puzzle: Hearthstone

Input file: *standard input*
Output file: *standard output*
Time limit: 2 seconds
Memory limit: 256 mebibytes

Hearthstone is one of the popular video games. **Please read the following rules carefully. They are different from the usual rules.**

There are n kinds of secret cards numbered $1, 2, \dots, n$. There are two types of events about secrets:

- **add**: Add a secret with an unknown number into the hero zone. No two secrets with the same number can be in the hero zone simultaneously.
- **test** x y : Test whether secret x exists. If secret x exists, then $y = 1$ and secret x is removed from the hero zone; otherwise, $y = 0$. Note that whatever y is, secret x does not exist in the hero zone after **testing** x .

An event sequence $E = [e_1, \dots, e_m]$ is valid if and only if it is possible to assign a number from 1 to n for each **add** event and perform the events $e_1, e_2, \dots, e_m$ in order such that:

- no secrets are in the hero zone at the beginning;
- secret x does not exist right before an event which **adds** a secret x ;
- secret x exists right before an event **test** x 1 ;
- secret x does not exist right before an event **test** x 0 .

Given q events $e_1, e_2, \dots, e_q$, you need to maintain an event sequence E . Initially, E is empty. For each $i = 1, 2, \dots, q$ in order, try to append e_i to the end of E . If E is invalid, remove e_i and report a bug. Otherwise, find the number of secrets that must exist in the hero zone and the number of secrets that must not exist in the hero zone after performing the events of E in order.

Note that the number of *secrets that must (not) exist* is not just the *number of* (non-)existing secrets. For example, if $n = 2$, initially, secret 1 is missing and secret 2 is missing, so the answers would be 0 and 2. After a single **add**, secret 1 is unknown (can be or not be in hero zone) and secret 2 is unknown, so the answers are 0 and 0. After **test** 2 0, secret 2 is missing, so we know the added one was certainly secret 1, so secret 1 is present, and the answers are 1 and 1. See examples for better understanding.

Input

There are multiple test cases. The first line of input contains an integer T ($1 \leq T \leq 10^5$), the number of test cases. For each test case:

The first line contains two integers n and q ($1 \leq n, q \leq 10^5$), the number of kinds of secrets and the number of events.

The i -th line of the following q lines represents e_i and contains:

- either a string “**add**”;
- or a string “**test**” followed by two integers x and y ($1 \leq x \leq n, 0 \leq y \leq 1$).

It is guaranteed that both the sum of n and the sum of q over all test cases do not exceed 10^5 .

Output

For each test case:

For each event, if it can be appended, output two integers: the number of secrets that must exist in the hero zone and the number of secrets that must not exist in the hero zone; otherwise, output the string “bug”.

Examples

<i>standard input</i>	<i>standard output</i>
2 1 8 test 1 0 test 1 1 add test 1 0 test 1 1 add test 1 1 test 1 0 2 10 add add add test 1 1 test 1 1 add add add test 2 1 test 2 1	0 1 bug 1 0 bug 0 1 1 0 0 1 0 1 0 0 2 0 bug 1 1 bug 2 0 bug bug 1 1 bug
1 4 7 add add test 3 0 test 4 0 add test 1 1 test 3 1	0 0 0 0 0 1 2 2 2 0 1 1 1 3

Problem D. Poker Game: Decision

Input file: *standard input*
Output file: *standard output*
Time limit: 8 seconds
Memory limit: 256 mebibytes

Alice and Bob invent a new game based on Texas hold'em. **Please read the following rules carefully as they are different from the usual rules. The background of this problem is exactly the same as problem E.**

There are 13 ranks, which are A, K, Q, J, T, 9, 8, 7, 6, 5, 4, 3, and 2 from high to low. There are 4 suits, which are S, H, C, and D. Every combination of a rank and a suit occurs exactly once, so there are $52 (= 13 \times 4)$ cards.

A hand is a set of five cards. Each hand has a rank. There are 10 types of hands. Each type also has a rank. If two hands are of different types, the hand of the type with a higher rank always ranks higher. A hand can be represented as a sequence $(r_1, r_2, r_3, r_4, r_5)$, where r_i is the rank of the i -th card and the order of the five cards depends on the type of the hand. If two hands are of the same type, the hand represented as the lexicographically larger sequence ranks higher: formally, if we find the smallest index i such that r_i of two hands are different, the hand with higher r_i ranks higher. If the types and the sequences r of two hands are equal, two hands have the same rank.

The 10 types are given below, from lowest to highest rank. If a hand matches the patterns of multiple types, it belongs to the one with the highest rank.

- **Highcard:** Any five cards. The sequence r satisfies $r_1 > r_2 > r_3 > r_4 > r_5$.
- **Pair:** Two cards with the same rank. The sequence r satisfies $r_1 = r_2, r_3 > r_4 > r_5$.
- **Two pairs:** Two cards with the same rank and another two cards with the same rank. The sequence r satisfies $r_1 = r_2 > r_3 = r_4$.
- **Three of a kind:** Three cards with the same rank. The sequence r satisfies $r_1 = r_2 = r_3, r_4 > r_5$.
- **Straight:** Five cards with five consecutive ranks. The sequence r satisfies $r_1 > r_2 > r_3 > r_4 > r_5$. Additionally, A 2 3 4 5 is a straight, and A is regarded as a rank lower than 2 in this case. Hence A 2 3 4 5 is the straight with the lowest ranks.
- **Flush:** Five cards with the same suit. The sequence r satisfies $r_1 > r_2 > r_3 > r_4 > r_5$.
- **Full house:** Three cards with the same rank and another two cards with the same rank. The sequence r satisfies $r_1 = r_2 = r_3, r_4 = r_5$.
- **Four of a kind:** Four cards with the same rank. The sequence r satisfies $r_1 = r_2 = r_3 = r_4$.
- **Straight flush:** A straight with the same suit. The sequence r satisfies $r_1 > r_2 > r_3 > r_4 > r_5$. Additionally, A 2 3 4 5 with the same suit is a straight flush, and A is regarded as a rank lower than 2 in this case. Hence A 2 3 4 5 with the same suit is the straight flush with the lowest ranks.
- **Royal flush:** Straight flush with the ranks T, J, Q, K, and A. Four different royal flushes are of the same rank.

Two cards are dealt to each of Alice and Bob. Instead of the regular rules, 6 community cards are dealt. Two players take community cards one by one, in turn, until each player has five cards, completing a hand. **Alice takes first.** The player who has a hand with higher rank wins. If two hands have same rank, there is a draw. **Note that all ten cards are shown to both, and they always choose the optimal strategy.**

The above are the same in problem E. The task is the following.

Given the cards of Alice, the cards of Bob and the 6 community cards, find the winner.

Input

There are multiple test cases. The first line of input contains an integer T ($1 \leq T \leq 10^5$), the number of test cases. For each test case:

The first line contains two strings a_1 and a_2 : Alice's initial cards.

The second line contains two strings b_1 and b_2 : Bob's initial cards.

The third line contains six strings c_1, c_2, c_3, c_4, c_5 , and c_6 : the community cards.

Each string is of length two. The first character is one of "A", "K", "Q", "J", "T", "9", "8", "7", "6", "5", "4", "3", "2", which represents the rank of a card. The second character is one of "S", "H", "C", "D", which represents the suit of a card.

It is guaranteed that all 10 given cards are pairwise distinct.

Output

For each test case:

Output the word "Alice" if Alice wins, "Bob" if Bob wins, or "Draw" if there is a draw.

Example

<i>standard input</i>	<i>standard output</i>
9	Alice
JC 4H	Bob
TS 5D	Draw
JS JH JD 4S 4C 4D	Alice
JC 4H	Bob
TS 5D	Draw
TH TC TD 5S 5H 5C	Alice
JC 4H	Bob
TS 5D	Draw
4S JS 5S TH TC TD	
7C 3C	
7H TH	
3S 3H 3D 2C 4H 5S	
7C 3C	
7H TH	
2H 4H 5H 6H 8H 9H	
7C 3C	
7H TH	
TS 3S 2S 2H 4C 4D	
2D KH	
4D JC	
2S 2H 2C KS KC KD	
2D KH	
4D JC	
4S 4H 4C JS JH JD	
2D KH	
4D JC	
2S KS 4S JS JH JD	

Problem E. Poker Game: Construction

Input file: *standard input*
Output file: *standard output*
Time limit: 2 seconds
Memory limit: 256 mebibytes

Alice and Bob invent a new game based on Texas hold'em. **Please read the following rules carefully as they are different from the usual rules. The background of this problem is exactly the same as problem D.**

There are 13 ranks, which are A, K, Q, J, T, 9, 8, 7, 6, 5, 4, 3, and 2 from high to low. There are 4 suits, which are S, H, C, and D. Every combination of a rank and a suit occurs exactly once, so there are $52 (= 13 \times 4)$ cards.

A hand is a set of five cards. Each hand has a rank. There are 10 types of hands. Each type also has a rank. If two hands are of different types, the hand of the type with a higher rank always ranks higher. A hand can be represented as a sequence $(r_1, r_2, r_3, r_4, r_5)$, where r_i is the rank of the i -th card and the order of the five cards depends on the type of the hand. If two hands are of the same type, the hand represented as the lexicographically larger sequence ranks higher: formally, if we find the smallest index i such that r_i of two hands are different, the hand with higher r_i ranks higher. If the types and the sequences r of two hands are equal, two hands have the same rank.

The 10 types are given below, from lowest to highest rank. If a hand matches the patterns of multiple types, it belongs to the one with the highest rank.

- **Highcard:** Any five cards. The sequence r satisfies $r_1 > r_2 > r_3 > r_4 > r_5$.
- **Pair:** Two cards with the same rank. The sequence r satisfies $r_1 = r_2, r_3 > r_4 > r_5$.
- **Two pairs:** Two cards with the same rank and another two cards with the same rank. The sequence r satisfies $r_1 = r_2 > r_3 = r_4$.
- **Three of a kind:** Three cards with the same rank. The sequence r satisfies $r_1 = r_2 = r_3, r_4 > r_5$.
- **Straight:** Five cards with five consecutive ranks. The sequence r satisfies $r_1 > r_2 > r_3 > r_4 > r_5$. Additionally, A 2 3 4 5 is a straight, and A is regarded as a rank lower than 2 in this case. Hence A 2 3 4 5 is the straight with the lowest ranks.
- **Flush:** Five cards with the same suit. The sequence r satisfies $r_1 > r_2 > r_3 > r_4 > r_5$.
- **Full house:** Three cards with the same rank and another two cards with the same rank. The sequence r satisfies $r_1 = r_2 = r_3, r_4 = r_5$.
- **Four of a kind:** Four cards with the same rank. The sequence r satisfies $r_1 = r_2 = r_3 = r_4$.
- **Straight flush:** A straight with the same suit. The sequence r satisfies $r_1 > r_2 > r_3 > r_4 > r_5$. Additionally, A 2 3 4 5 with the same suit is a straight flush, and A is regarded as a rank lower than 2 in this case. Hence A 2 3 4 5 with the same suit is the straight flush with the lowest ranks.
- **Royal flush:** Straight flush with the ranks T, J, Q, K, and A. Four different royal flushes are of the same rank.

Two cards are dealt to each of Alice and Bob. Instead of the regular rules, 6 community cards are dealt. Two players take community cards one by one, in turn, until each player has five cards, completing a hand. **Alice takes first.** The player who has a hand with higher rank wins. If two hands have same rank, there is a draw. **Note that all ten cards are shown to both, and they always choose the optimal strategy.**

The above are the same in problem D. The task is the following.

Given the cards of Alice and the cards of Bob, find possible 6 community cards such that Alice wins, that Bob wins, and that there is a draw.

Input

There are multiple test cases. The first line of input contains an integer T ($1 \leq T \leq 10^5$), the number of test cases. For each test case:

The first line contains two strings a_1 and a_2 : Alice's initial cards.

The second line contains two strings b_1 and b_2 : Bob's initial cards.

Each string is of length two. The first character is one of "A", "K", "Q", "J", "T", "9", "8", "7", "6", "5", "4", "3", "2", which represents the rank of a card. The second character is one of "S", "H", "C", "D", which represents the suit of a card.

It is guaranteed that all 4 given cards are pairwise distinct.

Output

For each test case:

Print a single line for each of the three questions: how to make Alice win, how to make Bob win, and how to make the game end in a draw. For each question, if it is possible, output "YES" and 6 strings representing the 6 cards; otherwise, output "NO".

The format of the cards in the output should be the same as the format in the input.

All 10 cards in input and output must be pairwise distinct.

Examples

<i>standard input</i>	<i>standard output</i>
3 JC 4H TS 5D 7C 3C 7H TH 2D KH 4D JC	YES JS JH JD 4S 4C 4D YES TH TC TD 5S 5H 5C YES 4S JS 5S TH TC TD YES 3S 3H 3D 2C 4H 5S YES 2H 4H 5H 6H 8H 9H YES TS 3S 2S 2H 4C 4D YES 2S 2H 2C KS KC KD YES 4S 4H 4C JS JH JD YES 2S KS 4S JS JH JD
2 AS AH AC AD AS AH 2S 2H	YES 2H 3S 4D 5C 6H 7S NO YES 2C 2D 3S 3H 4C 4D YES AC AD 3D 4C 5H 6S YES 2C 2D 3D 4C 5H 6S NO

Problem F. Longest Common Subsequence

Input file: *standard input*
Output file: *standard output*
Time limit: 2 seconds
Memory limit: 256 mebibytes

Given a sequence s of length n and a sequence t of length m , find the length of the longest common subsequence of s and t .

Input

There are multiple test cases. The first line of input contains an integer T ($1 \leq T \leq 10^3$), the number of test cases.

For each test case:

The only line contains seven integers: n, m, p, x, a, b , and c ($1 \leq n, m \leq 10^6$, $0 \leq x, a, b, c < p \leq 10^9$). Here, n is the length of s , and m is the length of t .

To avoid large input, you should generate the sequences as follows:

For each $i = 1, 2, \dots, n$ in order, update x to $(ax^2 + bx + c) \bmod p$, and then set s_i to x . And then, for each $i = 1, 2, \dots, m$ in order, update x to $(ax^2 + bx + c) \bmod p$, and then set t_i to x .

It is guaranteed that both the sum of n and the sum of m over all test cases do not exceed 10^6 .

Output

For each test case:

Output a single line with a single integer: the length of the longest common subsequence of s and t .

Example

<i>standard input</i>	<i>standard output</i>
2	0
4 3 1024 1 1 1 1	3
3 4 1024 0 0 0 0	

Note

In the first sample, $s = [3, 13, 183, 905]$ and $t = [731, 565, 303]$.

In the second sample, $s = [0, 0, 0]$ and $t = [0, 0, 0, 0]$.

Problem G. Lexicographic Comparison

Input file: *standard input*
Output file: *standard output*
Time limit: 2 seconds
Memory limit: 256 mebibytes

Consider a and p , two permutations of length n . Initially, $a_i = p_i = i$ for all $1 \leq i \leq n$. Let A be a sequence of permutations such that $A_1 = a$ and $A_{i,j} = A_{i-1,p_j}$ for all $i \geq 1$ and $1 \leq j \leq n$.

There are three types of operations, where x and y are positive integers:

1. **swap_a** x y : swap a_x and a_y , where $1 \leq x, y \leq n$;
2. **swap_p** x y : swap p_x and p_y , where $1 \leq x, y \leq n$;
3. **cmp** x y : compare A_x with A_y lexicographically.

For each operation of type 3, output the relationship between A_x and A_y . A permutation s is lexicographically smaller than a permutation t if and only if there exists an index i such that $s_i < t_i$ and $s_j = t_j$ for all $1 \leq j < i$.

Input

There are multiple test cases. The first line of input contains an integer T ($1 \leq T \leq 10^5$), the number of test cases. For each test case:

The first line contains an integer n and q ($1 \leq n, q \leq 10^5$), the length of the permutations and the number of operations.

Each of the following q lines contains one string f and two integers x and y representing an operation. The string f is one of “**swap_a**”, “**swap_p**”, and “**cmp**”. If f is “**swap_a**” or “**swap_p**” then $1 \leq x, y \leq n$. If f is “**cmp**” then $1 \leq x, y \leq 10^{18}$.

It is guaranteed that both the sum of n and the sum of q over all tests do not exceed 10^5 .

Output

For each test case:

For each query, output “<” if A_x is lexicographically smaller than A_y ; output “>” if A_x is lexicographically greater than A_y (in other words, A_y is lexicographically smaller than A_x); output “=” if $A_x = A_y$.

Example

<i>standard input</i>	<i>standard output</i>
2	=
5 5	<
cmp 1 2	>
swap_p 1 2	
cmp 1 2	
swap_a 1 2	
cmp 1 2	
1 1	
swap_a 1 1	

Problem H. Expression Evaluation

Input file: *standard input*
Output file: *standard output*
Time limit: 2 seconds
Memory limit: 256 mebibytes

Expression evaluation is a classic problem. In this problem, you only need to evaluate an expression of length less than 10^5 . It may only contain non-negative integers (possibly with leading zeros), and also operations '+', '-', and '*'. Formally, it satisfies the following grammar:

```
<expression>:= <term>|<expression>+<term>|<expression>-<term>
<term>:= <number>|<term>*<number>
<number>:= <digit>|<number><digit>
<digit>:= 0|1|2|3|4|5|6|7|8|9
```

For example, 013, 0213-2132*0213 are valid, but -2132 and 32113+-3213 are invalid.

The result of the evaluation may be too large or negative. Output the result modulo 2^{32} to avoid overflow since you will use a custom 32-bit machine to evaluate the expression.

The 32-bit machine contains 2^{10} units of memory, denoted as $r[0], r[1], \dots, r[2^{10} - 1]$. Each unit is a 32-bit unsigned integer, also working as an instruction. The machine's input is an expression described above, and the machine's output is the value of that expression modulo 2^{32} .

In each cycle, let $pc = r[0] \bmod 2^{10}$. The machine executes the instruction $r[pc]$. Consider the expansion $r[pc] = a2^{30} + b2^{20} + c2^{10} + d$ at the beginning of cycle, where a, b, c, d are non-negative integers less than 2^{10} :

- If $a = 0$, the machine outputs the value of $r[b]$ and stops.
- If $a = 1$, and then:
 - If there are no characters in input left, set $r[0]$ to $r[d]$;
 - Otherwise, set $r[b]$ to the ASCII code of the next character of input, and then set $r[0]$ to $r[c]$.
- If $a = 2$, set $r[b]$ to $(r[b] + r[c]) \bmod 2^{32}$, and then set $r[0]$ to $r[d]$.
- If $a = 3$, and then:
 - If $r[b] = 0$, set $r[0]$ to the value of $r[c]$;
 - Otherwise, set $r[0]$ to the value of $r[d]$.

Note that if $b = 0$ in some instructions, $r[0]$ may be set more than once. Its value is the value set last after the cycle.

You need to set the initial value for each unit of memory so that, for any expression possible within the constraints, the machine can stop after a finite amount of cycles and output the result of the expression modulo 2^{32} .

Since there is a time limit for testing, in this problem, the machine can execute at most 10^8 cycles.

Input

The only line contains a 32-bit unsigned integer: the seed for the expression generator.

You do not need to use it. It is just for the checker to generate the expressions.

Output

Output 2^{10} 32-bit unsigned integers in the only line: the initial values of the memory units.



Example

<i>standard input</i>	<i>standard output</i>
0	0 0 ... 0 (1024 zeros)

Note

The output in the example is wrong. It is given just to explain the output format.

Problem I. Equivalence in Connectivity

Input file: *standard input*
Output file: *standard output*
Time limit: 2 seconds
Memory limit: 256 mebibytes

Two undirected graphs of size n are equivalent in connectivity when there is a path from u to v in one graph if and only if there is a path from u to v in the other graph for all $1 \leq u < v \leq n$.

Given is a sequence of k graphs $G_1, G_2, \dots, G_k$. Each graph is of size n . In this sequence, for each $i = 2, 3, \dots, k$, there exists $p_i < i$ such that G_i can be obtained from G_{p_i} by adding or removing an edge. Divide the given graphs into groups: two graphs must be in the same group if and only if they are equivalent in connectivity.

Input

There are multiple test cases. The first line of input contains an integer T ($1 \leq T \leq 10^5$), the number of test cases. For each test case:

The first line contains three integers k , n , and m ($1 \leq k, n \leq 10^5$, $0 \leq m \leq \min\left(10^5, \frac{n(n-1)}{2}\right)$): the number of graphs, the number of vertices in each graph, and the number of edges in G_1 .

Each of the following m lines contains two integers u and v ($1 \leq u < v \leq n$), denoting an edge of G_1 connecting u and v . It is guaranteed that there are no multiple edges in G_1 .

The i -th of the following $k-1$ lines contains an integer p_{i+1} , a string t_{i+1} , and two integers x_{i+1} and y_{i+1} ($1 \leq p_{i+1} \leq i$, $1 \leq x_{i+1} < y_{i+1} \leq n$). Each string t_{i+1} is either “add” or “remove”.

If t_{i+1} is “add”, then G_{i+1} is obtained from $G_{p_{i+1}}$ by adding an edge connecting x_{i+1} and y_{i+1} . It is guaranteed that this edge does not exist in $G_{p_{i+1}}$.

If t_{i+1} is “remove”, then G_{i+1} is obtained from $G_{p_{i+1}}$ by removing an edge connecting x_{i+1} and y_{i+1} . It is guaranteed that this edge exists in $G_{p_{i+1}}$.

It is guaranteed that the sum of n , the sum of m , and the sum of k in all test cases do not exceed 10^5 .

Output

For each test case:

On the first line, output an integer r : the number of groups.

For each group, output a single line which contains an integer k followed by k integers: the size of the group and the numbers of graphs in the group.

You can output the groups and the graphs in any order.

Example

<i>standard input</i>	<i>standard output</i>
2	7
15 11 8	2 10 13
6 11	5 2 3 4 5 8
1 6	3 1 7 11
6 9	1 14
6 8	2 6 12
1 2	1 9
1 5	1 15
9 10	5
2 5	3 2 4 9
1 add 3 11	6 5 6 7 8 10 12
1 add 2 3	2 1 14
3 add 5 8	2 3 11
4 add 5 11	1 13
3 add 7 10	
1 add 6 10	
3 add 3 10	
1 remove 6 8	
5 add 4 9	
1 add 2 9	
8 add 7 8	
3 add 2 4	
1 remove 6 9	
10 remove 6 9	
14 5 2	
1 5	
1 4	
1 add 2 4	
1 add 3 4	
1 add 2 4	
4 add 3 4	
4 add 1 3	
5 add 1 3	
2 add 2 3	
1 add 1 2	
4 add 3 4	
3 add 4 5	
9 add 2 3	
3 remove 1 5	
3 remove 3 4	

Problem J. Symmetry: Tree

Input file: *standard input*
Output file: *standard output*
Time limit: 2 seconds
Memory limit: 256 mebibytes

Given a tree with n vertices, for each node $i = 1, 2, \dots, n$, find an integer point $p_i = (x_i, y_i)$, and then, for each edge (u, v) , connect points p_u and p_v with a line segment, so that the following conditions hold:

1. No two points coincide.
2. No two line segments have common points except at both endpoints.
3. There exists a line such that the shape formed by the points is symmetric about the line and the shape formed by the line segments is symmetric about the line.

Input

There are multiple test cases. The first line of input contains an integer T ($1 \leq T \leq 10^3$), the number of test cases. For each test case:

The first line contains an integer n ($1 \leq n \leq 10^3$), the number of vertices of the tree.

Each of the following $n - 1$ lines contains two integers u and v ($1 \leq u, v \leq n$, $u \neq v$), denoting an edge connecting u and v .

Note that there are **no constraints** related to the sum of n .

Output

For each test case:

If there is no answer, output the word “NO” on the only line.

Otherwise, output “YES” on the first line, and two integers x_i and y_i ($0 \leq |x_i|, |y_i| \leq n$) in the i -th of the following n lines.

After that, output another line with three integers a, b, c ($0 \leq |a|, |b|, |c| \leq n$), denoting that the shapes are symmetric about the $ax + by + c = 0$.

If there are multiple answers, output any one of them.

Example

<i>standard input</i>	<i>standard output</i>
5	YES
4	1 0
3 2	-2 0
1 3	-1 0
4 1	2 0
4	1 0 0
2 4	YES
1 4	1 0
3 4	0 1
9	-1 0
9 7	0 0
4 9	1 0 0
8 4	YES
4 6	0 3
1 8	-2 0
2 6	0 0
5 1	0 1
3 4	0 4
10	-1 0
5 3	2 0
4 5	0 2
6 4	1 0
2 5	1 0 0
5 8	NO
4 9	NO
7 8	
1 2	
10 6	
7	
2 7	
7 4	
7 5	
6 2	
4 3	
2 1	

Problem K. Symmetry: Convex

Input file: *standard input*
Output file: *standard output*
Time limit: 2 seconds
Memory limit: 256 mebibytes

Given is a strictly convex polygon with n vertices $p_1, p_2, \dots, p_n$ in counterclockwise. Denote C_i as the polygon with i vertices $p_1, p_2, \dots, p_i$. For each $i = 3, 4, \dots, n$, find the lines which C_i is symmetric about.

Input

There are multiple test cases. The first line of input contains an integer T ($1 \leq T \leq 10^5$), the number of test cases. For each test case:

The first line contains an integer n ($3 \leq n \leq 3 \cdot 10^5$), the number of vertices.

The i -th of the following n lines contains two integers x_i, y_i ($-10^9 \leq x_i, y_i \leq 10^9$), the coordinates of p_i .

It is guaranteed that the vertices are given counterclockwise, and the polygon is strictly convex, that is, no three vertices are collinear.

It is guaranteed that the sum of n in all test cases does not exceed $3 \cdot 10^5$.

Output

For each test case:

For each $i = 3, 4, \dots, n$, on the first line, output an integer k : the number of lines which C_i is symmetric about.

In each of the following k lines, output three integers a, b, c ($-2 \cdot 10^{18} \leq a, b, c \leq 2 \cdot 10^{18}$), denoting that C_i is symmetric about the line $ax + by + c = 0$.

If there are multiple answers, you can output any of them. For each i , you can output the lines in any order.

Example

<i>standard input</i>	<i>standard output</i>
3	1
4	1 1 -1
0 0	4
1 0	1 -1 0
1 1	0 2 -1
0 1	2 0 -1
3	1 1 -1
0 0	0
3 0	1
1 1	1 1 0
4	4
-1000000000 -1000000000	1 -1 0
1000000000 -1000000000	0 1 0
1000000000 1000000000	1 0 0
-1000000000 1000000000	1 1 0

Problem L. Symmetry: Closure

Input file: *standard input*
Output file: *standard output*
Time limit: 2 seconds
Memory limit: 256 mebibytes

A point set S is symmetric about a line ℓ if and only if there exists $s' \in S$ satisfying that s' and s are symmetric about the line ℓ for all $s \in S$.

Let us denote the distance between two points a and b as $d(a, b)$. The distance between two non-empty point sets A and B is $\inf \{d(a, b) : a \in A, b \in B\}$. The infimum of a non-empty real number set S is the maximum value of x which satisfies $x \leq s$ for all $s \in S$.

Lines $\ell_1, \ell_2, \dots, \ell_n$ are given, where two or more lines may coincide. For a point s , define $C(s)$ as the intersection of all sets S satisfying $s \in S$ such that S is symmetric about ℓ_i for all $i = 1, 2, \dots, n$.

There are q queries. For each query, given two points A and B , find the distance between $C(A)$ and $C(B)$.

Input

There are multiple test cases. The first line of input contains an integer T ($1 \leq T \leq 10^5$), the number of test cases. For each test case:

The first line contains an integer n and q ($1 \leq n, q \leq 10^5$): the number of lines and the number of points.

The i -th of the following n lines contains four integers x_{P_i} , y_{P_i} , x_{Q_i} , and y_{Q_i} : the coordinates of P_i and Q_i such that ℓ_i passes through P_i and Q_i . It is guaranteed that $x_{P_i} \neq x_{Q_i}$ or $y_{P_i} \neq y_{Q_i}$. Any two lines may coincide.

The i -th of the following q lines contains four integers x_{A_i} , y_{A_i} , x_{B_i} , and y_{B_i} : the coordinates of A_i and B_i .

It is guaranteed that the absolute value of all coordinates in the input does not exceed 10^9 .

It is guaranteed that both the sum of n and the sum of q over all test cases do not exceed 10^5 .

Output

For each test case:

For each query, output the distance between $C(A)$ and $C(B)$.

The distance you output will be considered correct if the relative error or absolute error to the jury does not exceed 10^{-9} .

